

APV



Way of Life!

Tangguh, Legaaa, Hemat Menguntungkan



GE

POWER STEERING

BLIND VAN

GA

FACE TO FACE



Side Impact Beam

Struktur pelindung benturan dari samping yang aman bagi penumpang maupun barang.



Air Intake dan Ground Clearance tinggi

Air intake (101 cm) serta ground clearance (175 mm) menjadikan APV terbukti tangguh melintasi genangan air maupun medan yang tidak rata.



TECT

TECT Total Effective Control Technology


TECT Body

TECT (Total Effective Control Technology) Body. Fitur keamanan yang berfungsi mengalihkan energi benturan. Teknologi ini secara progresif meningkatkan keamanan saat terjadi tabrakan.



Setting New Engine "Lebih Irit" 1.5L

Setting baru mesin G15A standar Euro 2 yang ramah lingkungan, berkapasitas 1.500cc injection, halus dan bertenaga, namun **irit konsumsi bahan bakar.**



Monocoque Body dengan Ladder Frame terpadu

kokoh, ringan sekaligus aman saat terjadi benturan

SPECIFICATION

DIMENSIONS / DIMENSI	BV	GA/GE
Overall length / Panjang keseluruhan (mm)	4.155	4.230
Overall width / Lebar keseluruhan (mm)		1.655
Overall height / Tinggi keseluruhan (mm)		1.865
Wheel base / Jarak poros roda (mm)		2.625
Tread / Jarak pijak		
Front / Depan (mm)	1.435	
Rear / Belakang (mm)	1.150	
Curb weight / Berat kendaraan (kg)	1.150	1.250
Gross vehicle weight / Berat kotor kendaraan (kg)		1.950
Ground clearance / Jarak terendah (mm)		180
Minimum turning radius / Radius putar minimum (m)		4,9
ENGINE / MESIN		
Type / Jenis		G15A
Cylinder / Silinder		4 in line
Number of valve / Jumlah katup		16
Piston Displacement / Isi silinder (cc)		1.493
Bore X stroke / Diameter X langkah (mm)		75,0 X 84,5
Maximum output / Daya maksimum (PS/rpm)		92,4/6.000
Maximum torque / Momen puntir maksimum (Nm/rpm)		126/3.000
Fuel distribution / Distribusi bahan bakar		Multi Point Injection
TRANSMISSION / TRANSMISI		
Type / Model		5-speed Manual
Gear Ratio / Perbandingan gigi		
	1st	4,545
	2nd	2,628
	3rd	1,865
	4th	1,241
	5th	1,000
Reverse / Mundur		4,431
Final gear ratio / Perbandingan gigi akhir		4,300
CHASSIS / RANGKA		
Steering / Sistem kemudi		Rack & Pinion
Suspension / Suspensi		McPherson Strut & Coil Spring
Rear / Belakang		Rigid Axle & Leaf Spring
Break / Rem		Ventilated Disc
Tire / Ban		Leading & trailing drum
		185/80 R14
SAFETY / KEAMANAN		
Seatbelt / Sabuk pengaman		Front 3-point ELR x 2
Air Intake / Posisi Air Intake		101cm

Standard and optional equipment available may vary for individual markets. Please enquire at your dealers, as specifications and illustrations may refer to model not available in your region. PT. Suzuki Indomobil Motor reserves the right to change, without prior notice, prices, colours, materials, equipment, specifications and models, and also to discontinue models.

COLORS



Radiant Red

Cool Black




Silky Silver

Graphite Grey

Diamond Blue

Warna tersedia untuk Tipe GEPS & GA
APV Delivery Van hanya tersedia dalam warna Putih

DIMENSION GA/GE



Sole Agent
PT. SUZUKI INDOMOBIL MOTOR
Jl. Diponegoro Km. 38,2 Temon-Bekasi

Sole Distributor
PT. SUZUKI INDOMOBIL SALES
Wijaya Industri 17 Floor, J. M T. Haryono Kari & Jember 13330

www.suzuki.co.id

